

# VENF.EX28665 - Flexible Sprinkler Hose with Fittings

## Flexible Sprinkler Hose with Fittings

**ATUSA GRUPO EMPRESARIAL S A**

EX28665

Pol Ind Atusa-Agurain S/N

Salvatierra

Alava, 01200 Spain

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
LFU30700	175	225	1x1/2	2.3 (700)	2	4	28	Limited
LFU31000	175	225	1x1/2	3.3(1000)	3	4	49	Limited
LFU31200	175	225	1x1/2	3.9(1200)	3	4	55	Limited
LFU31500	175	225	1x1/2	4.9(1500)	3	4	73	Limited
LFU31800	175	225	1x1/2	5.9(1800)	3	4	83	Limited
LFU40700	175	225	1x3/4	2.3(700)	2	4	30	Limited
LFU41000	175	225	1x3/4	3.3(1000)	3	4	51	Limited
LFU41200	175	225	1x3/4	3.9(1200)	3	4	56	Limited
LFU41500	175	225	1x3/4	4.9(1500)	3	4	74	Limited
LFU41800	175	225	1x3/4	5.9(1800)	3	4	83	Limited
LFB30700	175	225	1x1/2	2.3(700)	2	4	16	Limited
LFB31000	175	225	1x1/2	3.3(1000)	3	4	32	Limited
LFB31200	175	225	1x1/2	3.9(1200)	3	4	41	Limited
LFB31500	175	225	1x1/2	4.9(1500)	3	4	43	Limited
LFB31800	175	225	1x1/2	5.9(1800)	3	4	48	Limited
LFB40700	175	225	1x3/4	2.3(700)	2	4	17	Limited
LFB41000	175	225	1x3/4	3.3(1000)	3	4	41	Limited
LFB41200	175	225	1x3/4	3.9(1200)	3	4	43	Limited
LFB41500	175	225	1x3/4	4.9(1500)	3	4	44	Limited
LFB41800	175	225	1x3/4	5.9(1800)	3	4	47	Limited

Unbraided flexible sprinkler hose with fittings, LFU3 and LFU4 series are intended to be installed with ZJXT bracket assembly in accordance with the manufacturer's installation instructions dated 2021-10-18.

Braided flexible sprinkler hose with fittings, LFB3 and LFB4 series are intended to be installed with ZJXT bracket assembly in accordance with the manufacturer's installation instructions dated 2021-10-18.

Last Updated on 2021-10-22

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"