

## VIZA.EX15030 - Fittings, Grooved and Plain End

## Fittings, Grooved and Plain End

See General Information for Fittings, Grooved and Plain End

**ATUSA GRUPO EMPRESARIAL S A**

POL IND ATUSA-AGURAIN S/N

SALVATIERRA

01200 ALAVA, SPAIN

The following fittings are intended for use with Listed rubber gasketed fittings.


EX15030

**Grooved**

Model	Type	Size In.	Rated Pressure (psig)
90	90 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
90	90 Degree Elbow	33.7mm, 76.1mm	500
105	11.25 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	500
105	11.25 Degree Elbow	114.3mm, 139.7mm, 165.1mm, 168.3mm, 219.1mm	300
110	22.5 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	500
110	22.5 Degree Elbow	114.3mm, 139.7mm, 165.1mm, 168.3mm, 219.1mm	300
120	45 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
120	45 Degree Elbow	33.7mm	500
120	45 Degree Elbow	139.7mm	300
130	Tee	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12, 33.7mm, 76.1mm	500
130R	Reducing Tee	2 x 1-1/2;	500
		3 x 1, 2, 2-1/2;	
		4 x 2, 2-1/2, 3;	
		5 x 4;	
		6 x 2, 3, 4	
130R	Reducing Tee	60.3 x 33.7mm, 48.3mm	500
		76.1 x 42.4mm, 48.3mm, 60.3mm	
		88.9 x 42.4mm, 48.3mm, 60.3mm	
130R	Reducing Tee	114.3 x 60.3mm, 88.9mm	365
		168.3 x 60.3mm, 88.9mm,	

130R	Reducing Tee	88.9 x 76.1mm	300
		114.3 x 48.3mm, 76.1mm	
		139.7 x 114.3mm	
		165.1 x 60.3mm, 114.3mm, 139.7mm	
		168.3 x 76.1mm, 139.7mm	
		219.1 x 88.9mm, 114.3mm, 139.7mm	
		273.0 x 168.3mm	
180	Cross	1-1/2, 2, 2-1/2, 3, 4	500
240	Grooved Concentric Reducer	2 x 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1-1/4, 1-1/2, 2;	
		3 x 1-1/2, 2, 2-1/2;	
		4 x 1-1/2, 2, 2-1/2, 3;	
		5 x 3;	
		6 x 2, 2-1/2, 3, 4;	
		8 x 3, 4, 5, 6	
240	Grooved Concentric Reducer	42.4 x 33.7m	500
		48.3 x 42.4mm	
		76.1 x 42.4mm, 48.3mm, 60.3mm	
		88.9 x 76.1mm	
240	Grooved Concentric Reducer	114.3 x 76.1mm	300
		139.7 x 114.3mm	
		165.1 x 60.3mm, 88.9mm, 114.3mm, 139.7mm	
		168.3 x 76.1mm, 139.7mm	
		219.1 x 165.1mm	
		273.0 x 168.3mm, 219.1mm	
		323.9 x 219.1mm, 273.0mm	
300	Cap	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
300	Cap	33.7mm	500
300	Cap	139.7mm	300
315	Cap	88.9 x 60.3mm	365
		114.3 x 60.3mm	
		139.7 x 60.3mm	

		165.1 x 60.3mm	
316	Cap	88.9 x 48.3mm, 60.3mm	365
		114.3 x 60.3mm	
		139.7 x 60.3mm;	
		168.3 x 60.3mm	
		219.1 x 60.3mm	300
321	Flange Adapter	2, 2-1/2, 3, 4, 5, 6, 6-1/2 OD, 8	300
321	Flange Adapter	10, 12	225
321	Flange Adapter	33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm, 139.7mm, 165.1mm, 168.3mm	300
321	Flange Adapter	219.1mm, 273.1mm, 323.9mm	225
321 PN10	Flange Adapter	219.1mm, 273.0mm	225
90S	90 Degree Short Elbow	2, 2-1/2, 3 OD, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
90S	90 Degree Short Elbow	114.3mm, 165.1mm	365
130S	Short Tee	2, 2-1/2, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
130S	Short Tee	114.3mm, 165.1mm	365
90L	90 Degree Short Elbow	3, 4-1/4OD, 4, 5-1/4OD, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6, 10, 12	300
130L	Short Tee	3, 4-1/4OD, 4, 5-1/4OD, 5-1/2OD, 6-1/4OD, 6-1/2OD, 6, 8, 10, 12	300

Trademark and/or Tradename: 

Last Updated on 2020-10-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"