

## VIZM.EX15031 - Fittings, Rubber Gasketed

## Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)**ATUSA GRUPO EMPRESARIAL S A**

POL IND ATUSA-AGURAIN S/N

SALVATIERRA

01200 ALAVA, SPAIN

**Coupling**

EX15031

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
RN	Rolled	10	1-1/4, 1-1/2, 2-1/2	500
RN	Rolled	10	2, 3, 4, 5, 6	300
RN	Rolled	10	8	450
RN	Rolled	10	10, 12	300
RN	Rolled	1387-10	6-1/2 OD	300
RN	Rolled, Cut	40	1-1/4, 1-1/2	500
RN	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6	300
RN	Rolled, Cut	40	8	450
RN	Rolled, Cut	40	10, 12	300
RN	Rolled, Cut	1387-40	6-1/2 OD	300
RN	Rolled, Cut	4200	355.6 / 6.3mm	175
RS	Rolled	10	4	365
RS	Rolled	10	3, 6, 8	300
RS	Rolled	40	3, 4, 6, 8	300
RS	Rolled	1387-M	6-1/2 OD	300
RS	Rolled	1387-H	6-1/2 OD	300
RL	Rolled	10	1-1/4, 1-1/2, 3, 4, 8, 10	300

RL	Rolled, Cut	40	1-1/4, 1-1/2, 3, 4, 8, 10	300
RL	Rolled	GB/T 21835	3OD(4.5mm), 4-1/4OD(5.4mm) 5-1/4OD(5.6mm), 5-1/2OD(5.6mm) 6-1/4OD(6.3mm), 6-1/2OD(6.3mm)	300

**Flexible coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
FN/FR	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	300
FN/FR	Rolled	10	8	450
FN/FR	Rolled	1387-10	6-1/2 OD	300
FN/FR	Rolled	1387-M, 10	2-1/2 x 2;	300
			3 x 2, 2-1/2;	
			4 x 2, 2-1/2	
FN/FR	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	300
FN/FR	Rolled, Cut	40	8	450
FN/FR	Rolled, Cut	1387-40	6-1/2 OD	300
FN/FR	Rolled, Cut	1387-H, 40	2-1/2 x 2;	300
			3 x 2, 2-1/2;	
			4 x 2, 2-1/2, 3	
FN/FR	Rolled, Cut	4200	33.7 / 3.2mm	500
FN	Rolled, Cut	4200	273.0 / 6.3mm, 323.9 / 6.3mm	225
FN/FR	Rolled, Cut	4200	60.3 / 3.2 x 48.3 / 4.0mm	300
FL	Rolled	10	6, 8, 10	300
FL	Rolled, Cut	40	6, 8, 10	300

**Side outlet**

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (psig)
DA1	Threaded	4200	42.4 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm	300
			48.3 / 4.0 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm	
			60.3 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm	
DS1	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2;	300
			3 x 1, 1-1/4, 1-1/2, 2	
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	

			5 x 2;	
			6 x 1-1/4, 1-1/2, 2, 3	
DS1	Threaded	1387-M, 1387-H	6-1/2 OD x 1-1/2, 2, 2-1/2	300
DS1	Threaded	10	3 x 1/2, 3/4;	300
			4 x 1/2, 3/4;	
			8 x 2	
DS1	Threaded	4200	60.3 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm;	300
			76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm;	
			159.0 / 4.5mm x 60.3mm	
DS2	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2;	300
			3 x 1-1/4, 1-1/2, 2	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3	
			5 x 1-1/4, 2, 2-1/2,	
			6 x 1-1/4, -1/2, 2, 2-1/2, 3, 4	
DS2	Grooved	1387-M, 1387-H 10	6-1/2 OD x 2, 2-1/2;	300
DS2	Grooved		8 x 2, 2-1/2, 3, 4	300
DS2	Grooved	4200	76.1 / 3.6 x 33.7 / 3.2mm	300
			139.7 / 3.6mm x 42.4mm	
			273.0 / 6.3 x 114.3 / 3.6mm	
DD1	Threaded	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	300
			5 x 2, 3; 6 x 1-1/4, 1-1/2, 2, 3	
DD1	Threaded	1387-M, 1387-H	6-1/2 OD x 2, 2-1/2	300
DD2	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	300
			5 x 1-1/4, 2, 2-1/2; 6 x 1-1/2, 2, 2-1/2, 3, 4	
DD3	Threaded and Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	300
			5 x 2; 6 x 1-1/2, 2, 3	
DD3	Threaded and Grooved	1387-M, 1387-H	6-1/2 OD x 2, 2-1/2	300


Suitable for use in dry pipe systems for temperatures to -40 F

10 refers to Schedule 10 steel pipe in accordance with NFPA 13

40 refers to Schedule 40 steel pipe in accordance with NFPA 13

1387-10 refers to BS 1387 Schedule 10 steel pipe

1387-40 refers to BS 1387 Schedule 40 steel pipe

Trademark and/or Tradename: 

Last Updated on 2020-10-13

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"