

HLXS.EX27278 - Butterfly Valves

Butterfly Valves

[See General Information for Butterfly Valves](#)**ATUSA GRUPO EMPRESARIAL S A**

POL IND ATUSA-AGURAIN S/N

SALVATIERRA

01200 ALAVA, SPAIN

EX27278

Model	Size, NPS	Body Type	Pressure Rating, psig (Bar)	Indicator Post	Supervisory Switch*
Butterfly valve					
630-300	2, 2.5, 2.5 (76.1 mm), 3 4, 5, 5 (139.7 mm), 6 6 (165.1 mm) 8, 10, 12	Groove	300	N/A	N/A
630-250			250		
630-200			200		
630-175			175		
630-PN16			300		
630-PN10			300		
635-300	2, 2.5, 2.5 (76.1 mm), 3 4, 5, 5 (139.7 mm), 6 6 (165.1 mm) 8, 10, 12	Groove	300		I, O
635-250			250		
635-200			200		
635-175			175		
635-PN16			300		
635-PN10			300		
637	2,2.5,3,4,5,6 8,10,12	Wafer	363		
636	2,2.5,3,4,5,6 8,10,12	Wafer	363		
639-300	2,2.5,3,4,5,6 8,10,12	Lug	300		
639-PN16	2,2.5,3,4,5,6 8,10,12	Lug	363		
639-PN10	2,2.5,3,4,5,6 8,10,12	Lug	363		
638-300	2,2.5,3,4,5,6 8,10,12	Lug	300		
638-PN16	2,2.5,3,4,5,6 8,10,12	Lug	363		
638-PN10	2,2.5,3,4,5,6 8,10,12	Lug	363		
634	1, 1-1/4, 1-1/2, 2	Threaded	175	N/A	I/O

* I = Indoor installation; O = Outdoor installation

Note:

The shaft material designation for groove end configuration is SS431, for wafer or lug end configuration is SS420.

Models 630-300, 630-250, 630-200, 630-175, 630-PN16, 630-PN10, with gear box but no micro-switches inside; Models 635-300, 635-250, 635-200, 635-175, 635-PN16, 635-PN10, with gear box with micro-switches inside.

Models 635-300, 635-250, 635-200, 635-175, 635-PN16, 635-PN10, 630-300, 630-250, 630-200, 630-175, 630-PN16, 630-PN10 series have groove end configurations.

Model name end with "-300/250/200" means connect with flange comply with ASME B16.5, class 150; Model name end with "-PN16/PN10" means connect with flange comply with EN 1092, PN10/16; Wafer butterfly valves are of universal flange standard design; Lug butterfly valves can accommodate the different flange standards by modification on the drilling.

Last Updated on 2018-12-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"