



Fig. 241

TUERCA DE REDUCCIÓN LATÓN M/H

BUSHINGS BRASS M/F



INFORMACIÓN TÉCNICA - TECHNICAL INFORMATION

DN	COD.	DIMENSIONES - DIMENSIONS			Peso aprox. Weight aprox. (g)
		L (mm)	G (inches)	G1 (inches)	
1/4" x 1/8"	LS241010	10,0	1/4"	1/8"	5
3/8" x 1/8"	LS241020	13,0	3/8"	1/8"	13
3/8" x 1/4"	LS241021	13,0	3/8"	1/4"	10
1/2" x 1/4"	LS241031	14,5	1/2"	1/4"	25
1/2" x 3/8"	LS241032	14,5	1/2"	3/8"	15
3/4" x 3/8"	LS241042	15,0	3/4"	3/8"	35
3/4" x 1/2"	LS241043	16,0	3/4"	1/2"	27
1" x 1/2"	LS241053	17,5	1"	1/2"	63
1" x 3/4"	LS241054	17,5	1"	3/4"	46
1 1/4" x 1/2"	LS241063	19,5	1 1/4"	1/2"	114
1 1/4" x 3/4"	LS241064	19,5	1 1/4"	3/4"	96
1 1/4" x 1"	LS241065	19,5	1 1/4"	1"	73
1 1/2" x 1/2"	LS241073	20,5	1 1/2"	1/2"	131
1 1/2" x 3/4"	LS241074	20,5	1 1/2"	3/4"	140
1 1/2" x 1"	LS241075	20,5	1 1/2"	1"	119
1 1/2" x 1 1/4"	LS241076	20,5	1 1/2"	1 1/4"	73
2" x 1/2"	LS241083	25,5	2"	1/2"	235
2" x 3/4"	LS241084	25,5	2"	3/4"	224
2" x 1"	LS241085	25,5	2"	1"	217
2" x 1 1/4"	LS241086	25,5	2"	1 1/4"	215
2" x 1 1/2"	LS241087	25,5	2"	1 1/2"	168
2 1/2" x 1 1/4"	LS2410A6	28,0	2 1/2"	1 1/4"	346
2 1/2" x 1 1/2"	LS2410A7	28,0	2 1/2"	1 1/2"	329
2 1/2" x 2"	LS2410A8	28,0	2 1/2"	2"	310
3" x 2"	LS2410B8	33,0	3"	2"	596
3" x 2 1/2"	LS2410BA	33,0	3"	2 1/2"	375
4" x 2"	LS2410D8	44,0	4"	2"	930
4" x 2 1/2"	LS2410DA	44,0	4"	2 1/2"	898
4" x 3"	LS2410DB	44,0	4"	3"	970

 Rev.2-04.20
1/2



CARACTERÍSTICAS BÁSICAS

- Cuerpo en latón CW617N-DW según UNE-EN 12165.
- Método de fabricación: Forja en caliente.
- Rosca de unión según UNE-EN ISO 228-1.
- Accesorios conforme a la norma UNE-EN 1254-4.
- Rango de temperatura de trabajo: -20 a 130 °C.
- Presión máxima de ejercicio: PN 25.

APLICACIONES GENERALES

- Agua sanitaria fría y caliente.

INSTRUCCIONES DE MONTAJE

- Aplicar en la rosca teflón o sellante similar para obtener una mayor estanqueidad en la unión.
- Evitar el exceso del material añadido para prevenir posibles roturas por el excesivo apriete.
- Colocar el accesorio en la instalación, con atención de no exceder el apriete de la pieza.

Observaciones:

Dada la complejidad, variedad y gran cantidad de especificaciones particulares de cada instalación, en conjunción con la existencia de diversos factores que pueden afectar a las condiciones de trabajo y naturaleza del producto, es responsabilidad del usuario final realizar los ensayos necesarios para garantizar el correcto funcionamiento del producto en cada aplicación concreta.

La instalación del producto deberá realizarse y mantenerse siguiendo códigos de buena práctica y/o estándares existentes.

BASIC FEATURES

- Body in brass CW617N-DW according to EN 12165.
- Production method: Hot forging.
- Threads according to EN ISO 228-1.
- Fittings comply with EN 1254-4 standard.
- Working temperature range: -20 to 130 °C.
- Maximal working pressure: PN 25.

GENERAL APPLICATIONS

- Cold and hot sanitary water.

ASSEMBLING INSTRUCTIONS

- Place over the fitting PTFE or similar sealant in order to obtain a better tightness on the coupling.
- Avoid any surplus of sealant in order to prevent possible breakings caused by excessive clamping.
- Connect the fitting with the installation. Pay attention to not exceeding in fitting clamping.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Debido al constante desarrollo de nuestros productos, los datos suministrados pueden ser alterados sin previo aviso.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.2-04.20
2/2