


Fig. 241

RACCORDI FILETTATI IN ACCIAIO INOX - NIPPO RIDUZIONE

THREADED STAINLESS STEEL FITTING - REDUCING BUSH



PN 10



INFORMAZIONI TECNICHE - TECHNICAL INFORMATION

DN	COD.	DIMENSIONI - DIMENSIONS				Peso appros. Weight aprox. (kg)
		A (mm)	E (mm)	L (mm)	M (mm)	
1/2" x 1/4"	I241L031	22,0	16,5	13,5	5,0	0,022
1/2" x 3/8"	I241L032	22,0	16,5	13,5	5,0	0,018
3/4" x 1/2"	I241L043	27,5	22,0	14,5	5,5	0,035
1" x 1/2"	I241L053	34,0	28,1	14,5	6,0	0,054
1" x 3/4"	I241L054	34,0	28,1	14,5	6,0	0,055
1 1/4" x 1/2"	I241L063	43,5	36,5	19,0	6,5	0,095
1 1/4" x 3/4"	I241L064	43,5	36,5	19,0	6,5	0,114
1 1/4" x 1"	I241L065	42,6	35,0	21,0	6,0	0,075
1 1/2" x 1/2"	I241L073	49,0	42,2	20,5	7,0	0,141
1 1/2" x 3/4"	I241L074	49,5	42,2	19,0	6,5	0,129
1 1/2" x 1"	I241L075	49,5	42,2	19,0	6,5	0,125
1 1/2" x 1 1/4"	I241L076	49,5	42,2	19,0	6,5	0,085
2" x 1/2"	I241L083	61,0	52,0	24,0	7,5	0,251
2" x 3/4"	I241L084	61,0	52,0	24,0	7,5	0,242
2" x 1"	I241L085	61,0	52,0	24,0	7,5	0,220
2" x 1 1/4"	I241L086	61,0	52,0	24,0	7,5	0,252
2" x 1 1/2"	I241L087	61,0	52,0	24,0	7,5	0,206

CARATTERISTICHE FONDAMENTALI

- Realizzato in acciaio inossidabile austenitico AISI 316 con trattamento termico standard.
- Metodo di produzione: Fusione.
- Filettature conformi la norma UNI EN 10226-1 / ISO 7-1 (tipo R-Rp).
- Temperatura di esercizio: da -20 a 220 °C.
- Pressione di esercizio: PN 10.

APPLICAZIONI GENERALI

- Acqua, aria, vapore, oli e gas.

Osservazioni:

Data la complessità, la varietà e l'elevato numero di specifiche particolari di ciascuna installazione, unitamente all'esistenza di vari fattori che possono influenzare le condizioni di lavoro e la natura del prodotto, è responsabilità dell'utente finale eseguire le prove necessarie per garantire il corretto funzionamento del prodotto in ogni specifica applicazione.

L'installazione del prodotto deve essere eseguita e mantenuta secondo codici di buona pratica e/o norme vigenti.

BASIC FEATURES

- Made of austenitic stainless steel AISI 316 with standard heat treatment.
- Production method: Fusion.
- Threads according to EN 10226-1 / ISO 7-1 (type R-Rp).
- Working temperature range: -20 to 220 °C.
- Maximal working pressure: PN 10.

GENERAL APPLICATIONS

- Water, air, steam, oil and gas.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota: A causa del costante sviluppo dei nostri prodotti, i dati forniti possono essere modificati senza preavviso.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.1-07.23



Polígono Industrial ATUSA - Agurain S/N - 01200 Salvatierra (Alava) España
Tel.: (+34) 945 18 00 00 Fax : (+34) 945 30 01 53 e-mail: ventas@atusagroup.com
www.atusagroup.com