


Fig. 241

ACESSÓRIO INOXIDÁVEL ROSCADO - PORCA DE REDUÇÃO
THREADED STAINLESS STEEL FITTING - REDUCING BUSH


ISO 4144


INFORMAÇÃO TÉCNICA - TECHNICAL INFORMATION

DN	COD.	DIMENSÕES - DIMENSIONS					Peso aprox. Weight approx. (kg)
		A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	
1/4" x 1/8"	I2416010	8,4	15,0	12,0	12,5	19,0	0,010
3/8" x 1/8"	I2416020	11,0	19,0	13,0	14,0	20,3	0,025
3/8" x 1/4"	I2416021	11,0	19,0	13,0	14,0	20,3	0,020
1/2" x 1/4"	I2416031	15,0	22,5	15,0	17,0	23,7	0,035
1/2" x 3/8"	I2416032	15,0	22,5	14,0	17,0	23,7	0,030
3/4" x 1/4"	I2416041	20,5	29,0	16,4	18,0	26,0	0,065
3/4" x 3/8"	I2416042	20,5	29,0	16,3	18,0	26,0	0,060
3/4" x 1/2"	I2416043	20,5	29,0	15,8	18,0	26,0	0,050
1" x 1/2"	I2416053	26,0	35,5	17,4	19,0	27,0	0,085
1" x 3/4"	I2416054	26,0	35,5	13,6	19,0	27,0	0,070
1 1/4" x 1/2"	I2416063	34,5	43,6	20,2	20,5	30,0	0,145
1 1/4" x 3/4"	I2416064	34,5	43,6	18,2	20,5	30,0	0,135
1 1/4" x 1"	I2416065	34,5	43,6	16,0	20,5	30,0	0,115
1 1/2" x 1/2"	I2416073	40,0	51,0	22,0	22,0	31,0	0,200
1 1/2" x 3/4"	I2416074	40,0	51,0	20,0	22,0	31,0	0,195
1 1/2" x 1"	I2416075	40,0	51,0	17,0	22,0	31,0	0,180
1 1/2" x 1 1/4"	I2416076	40,0	51,0	15,5	22,0	31,0	0,120
2" x 1/2"	I2416083	51,0	62,4	26,0	26,0	35,0	0,265
2" x 3/4"	I2416084	51,0	62,4	23,0	26,0	35,0	0,330
2" x 1"	I2416085	51,0	62,4	21,0	26,0	35,0	0,330
2" x 1 1/4"	I2416086	51,0	62,4	20,0	26,0	35,0	0,270
2" x 1 1/2"	I2416087	51,0	62,4	17,8	26,0	35,0	0,235
2 1/2" x 1"	I2416095	64,5	77,8	27,0	27,0	40,0	0,635
2 1/2" x 1 1/4"	I2416096	64,5	77,2	25,0	27,0	40,0	0,600
2 1/2" x 1 1/2"	I2416097	64,5	77,8	25,0	27,0	40,0	0,570
2 1/2" x 2"	I2416098	64,5	77,8	24,0	27,0	39,5	0,425
3" x 2"	I24160A8	77,2	91,2	27,3	33,0	44,0	0,800
3" x 2 1/2"	I24160A9	77,2	91,2	20,0	33,0	44,0	0,560
4" x 2"	I24160C8	101,3	116,6	27,0	36,0	48,0	0,650
4" x 2 1/2"	I24160C9	101,3	116,6	25,0	36,0	48,0	1,415
4" x 3"	I24160CA	101,3	116,6	23,3	36,0	48,0	1,205

Rev.2- 11.20
1/2



CARACTERÍSTICAS BÁSICAS

- Fabricado em aço inoxidável austenítico AISI 316 com tratamento térmico normalizado.
- Método de fabrico: Fusão.
- Dimensões conformes norma ISO 4144.
- Roscas conformes norma NP EN 10226-1 / ISO 7-1 (tipo R-Rp).
- Temperatura de serviço: -20 a 220 °C.
- Pressão de serviço: PN 20.

APLICAÇÕES GERAIS

- Água, ar, vapor, óleos e gás.

Observações:

Dada a complexidade, variedade e grande quantidade de especificações particulares de cada instalação, em conjunção com a existência de diversos factores que podem afectar as condições de trabalho e natureza do produto, é da responsabilidade do utilizador final realizar os ensaios necessários para garantir o correcto funcionamento do produto em cada aplicação concreta.

A instalação do produto deverá ser realizada e mantida seguindo os códigos de boa prática e/ou normas existentes.

BASIC FEATURES

- Made of austenitic stainless steel AISI 316 with standard heat treatment.
- Production method: Fusion.
- Dimensions according to ISO 4144 standard.
- Threads according to EN 10226-1 / ISO 7-1 (type R-Rp).
- Working temperature range: -20 to 220 °C.
- Maximal working pressure: PN 20.

GENERAL APPLICATIONS

- Water, air, steam, oil and gas.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Devido ao constante desenvolvimento dos nossos produtos, o desenho e os dados fornecidos podem ser alterados sem aviso prévio.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.2-11.20
2/2