



ACESSÓRIOS DE COMPRESSÃO PARA TUBO PE-X - JOELHO MACHO

COMPRESSION FITTINGS FOR PE-X PIPES - MALE ELBOW



INFORMAÇÃO TÉCNICA - TECHNICAL INFORMATION

Ø	COD.	DIMENSÕES - DIMENSIONS					Peso aprox. Weight approx. (g)
		A (mm)	B (mm)	C (mm)	F (polegadas/inches)	G (mm)	
1/2" x 15 x 2,5	TR8CM153	28,2	10,0	7,0	G 1/2"	24,0	71
1/2" x 16 x 2,0	TR9CM163	28,2	12,0	9,5	G 1/2"	24,0	65
1/2" x 16 x 2,2	TR8CM163	28,2	11,6	9,0	G 1/2"	24,0	66
1/2" x 18 x 2,5	TR8CM183	37,5	13,0	10,0	G 1/2"	29,0	110
1/2" x 20 x 2,0	TR9CM203	39,5	16,0	12,5	G 1/2"	29,0	121
1/2" x 20 x 2,8	TR8CM203	39,5	14,4	11,0	G 1/2"	29,0	131
3/4" x 16 x 2,0	TR9CM164	36,5	12,0	9,5	G 3/4"	31,0	107
3/4" x 16 x 2,2	TR8CM164	36,5	11,6	9,0	G 3/4"	31,0	107
3/4" x 18 x 2,5	TR8CM184	38,5	13,0	10,0	G 3/4"	31,0	122
3/4" x 20 x 2,0	TR9CM204	39,0	16,0	12,5	G 3/4"	31,0	131
3/4" x 20 x 2,8	TR8CM204	39,0	14,4	11,0	G 3/4"	31,0	134
3/4" x 22 x 3,0	TR8CM224	43,0	16,0	12,0	G 3/4"	34,0	191
3/4" x 25 x 2,3	TR9CM254	45,0	20,4	16,5	G 3/4"	34,0	202
3/4" x 25 x 3,5	TR8CM254	45,0	18,0	14,0	G 3/4"	34,0	214
3/4" x 32 x 3,0	TR9CM324	50,0	26,0	21,0	G 3/4"	41,5	385
1" x 25 x 2,3	TR9CM255	45,0	20,4	16,5	G 1"	39,0	227
1" x 25 x 3,5	TR8CM255	45,0	18,0	14,0	G 1"	39,0	237
1" x 32 x 3,0	TR9CM325	50,0	26,0	21,0	G 1"	44,5	311

CARACTERÍSTICAS BÁSICAS

- Corpo em latão CW617N segundo NP EN 12165.
- Anilha em latão CW617N segundo NP EN 12164.
- Porca em latão CW617N segundo NP EN 12165.
- Acessórios conformes a norma NP EN 1254-3.
- Roscas de união conformes NP EN ISO 228-1.
- Temperatura de serviço: -20 °C a 95 °C.
- Pressão máxima de serviço: PN 10.

APLICAÇÕES GERAIS

- Água fria e quente em instalações hidro-sanitárias e aquecimento.

BASIC FEATURES

- Body in brass CW617N according to EN 12165.
- Ring in brass CW617N according to EN 12164.
- Nut in brass CW617N according to EN 12165.
- Fittings comply with the EN 1254-3 standard.
- Threads according to EN ISO 228-1.
- Working temperature range: -20 °C to 95 °C.
- Maximal working pressure: PN 10.

GENERAL APPLICATIONS

- Cold and hot water in sanitary and heating installations.

Rev.1-09.23

1/2



Polígono Industrial ATUSA - Agurain S/N - 01200 Salvatierra (Alava) España
Tel.: (+34) 945 18 00 00 Fax : (+34) 945 30 01 53 e-mail: ventas@atusagroup.com
www.atusagroup.com



INSTRUÇÕES DE MONTAGEM

- Cortar o tubo perpendicularmente ao seu eixo utilizando uma ferramenta corta-tubo apropriada.
- Eliminar a rebarba.
- Inserir a anilha e a porca no tubo.
- Inserir o tubo no corpo até chegar ao topo.
- Com uma chave hexagonal apertar a porca, tendo em atenção nunca exceder o binário de aperto da peça.

Observações:

Dada a complexidade, variedade e grande quantidade de especificações particulares de cada instalação, em conjugação com a existência de diversos factores que podem afectar as condições de trabalho e natureza do produto, é da responsabilidade do utilizador final realizar os ensaios necessários para garantir o correcto funcionamento do produto em cada aplicação concreta.

A instalação do produto deverá ser realizada e mantida seguindo os códigos de boa prática e/ou normas existentes.

ASSEMBLING INSTRUCTIONS

- Cut the pipe perpendicularly to its axis using an appropriate pipe-cutting tool.
- Remove possible residual burr.
- Insert nut and olive on the pipe.
- Insert the pipe into the body until the pipe stop.
- With an hexagonal spanner screw the nut. Pay attention to not exceeding in fitting clamping.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Devido ao constante desenvolvimento dos nossos produtos, o desenho e os dados fornecidos podem ser alterados sem aviso prévio.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.1-09.23

2/2