



ACESSÓRIOS DE COMPRESSÃO PARA TUBO PE-X - CASQUILHO FÊMEA

COMPRESSION FITTINGS FOR PE-X PIPES - FEMALE STRAIGHT COUPLING



INFORMAÇÃO TÉCNICA - TECHNICAL INFORMATION

Ø	COD.	DIMENSÕES - DIMENSIONS				Peso aprox. Weight aprox. (g)
		A (mm)	B (mm)	C (mm)	F (polegadas/inches)	
3/8" x 12 x 2,0	TR8RH122	35,0	8,0	5,0	G 3/8"	65
1/2" x 12 x 2,0	TR9RH123	32,0	8,0	5,0	G 1/2"	32
1/2" x 15 x 2,5	TR8RH153	32,0	10,0	7,0	G 1/2"	67
1/2" x 16 x 2,0	TR9RH163	32,0	12,0	9,5	G 1/2"	66
1/2" x 16 x 2,2	TR8RH163	32,0	11,6	9,0	G 1/2"	63
1/2" x 18 x 2,5	TR8RH183	33,5	13,0	10,0	G 1/2"	82
1/2" x 20 x 2,0	TR9RH203	36,0	16,0	12,5	G 1/2"	111
1/2" x 20 x 2,8	TR8RH203	36,0	14,4	11,0	G 1/2"	110
1/2" x 22 x 3,0	TR8RH223	42,0	16,0	12,0	G 1/2"	172
3/4" x 16 x 2,0	TR9RH164	34,5	12,0	9,5	G 3/4"	91
3/4" x 16 x 2,2	TR8RH164	34,5	11,6	9,0	G 3/4"	93
3/4" x 18 x 2,5	TR8RH184	37,0	13,0	10,0	G 3/4"	102
3/4" x 20 x 2,0	TR9RH204	39,0	16,0	12,5	G 3/4"	119
3/4" x 20 x 2,8	TR8RH204	39,0	14,4	11,0	G 3/4"	119
3/4" x 22 x 3,0	TR8RH224	38,5	16,0	12,0	G 3/4"	155
3/4" x 25 x 2,3	TR9RH254	44,0	20,4	16,5	G 3/4"	194
3/4" x 25 x 3,5	TR8RH254	44,0	18,0	14,0	G 3/4"	194
3/4" x 32 x 3,0	TR9RH324	44,5	26,0	21,0	G 3/4"	279
1" x 25 x 3,5	TR8RH255	46,0	18,0	14,0	G 1"	242
1" x 32 x 3,0	TR9RH325	42,0	26,0	21,0	G 1"	291

CARACTERÍSTICAS BÁSICAS

- Corpo em latão CW617N segundo NP EN 12165.
- Anilha em latão CW617N segundo NP EN 12164.
- Porca em latão CW617N segundo NP EN 12165.
- Acessórios conformes a norma NP EN 1254-3.
- Roscas de união conformes NP EN ISO 228-1.
- Temperatura de serviço: -20 °C a 95 °C.
- Pressão máxima de serviço: PN 10.

BASIC FEATURES

- Body in brass CW617N according to EN 12165.
- Ring in brass CW617N according to EN 12164.
- Nut in brass CW617N according to EN 12165.
- Fittings comply with the EN 1254-3 standard.
- Threads according to EN ISO 228-1.
- Working temperature range: -20 °C to 95 °C.
- Maximal working pressure: PN 10.

Rev.1-09.23

1/2



Polígono Industrial ATUSA - Agurain S/N - 01200 Salvatierra (Alava) España
Tel.: (+34) 945 18 00 00 Fax : (+34) 945 30 01 53 e-mail: ventas@atusagroup.com
www.atusagroup.com



APLICAÇÕES GERAIS

- Água fria e quente em instalações hidro-sanitárias e aquecimento.

INSTRUÇÕES DE MONTAGEM

- Cortar o tubo perpendicularmente ao seu eixo utilizando uma ferramenta corta-tubo apropriada.
- Eliminar a rebarba.
- Inserir a anilha e a porca no tubo.
- Inserir o tubo no corpo até chegar ao topo.
- Com uma chave hexagonal apertar a porca, tendo em atenção nunca exceder o binário de aperto da peça.

Observações:

Dada a complexidade, variedade e grande quantidade de especificações particulares de cada instalação, em conjunção com a existência de diversos factores que podem afectar as condições de trabalho e natureza do produto, é da responsabilidade do utilizador final realizar os ensaios necessários para garantir o correcto funcionamento do produto em cada aplicação concreta.

A instalação do produto deverá ser realizada e mantida seguindo os códigos de boa prática e/ou normas existentes.

GENERAL APPLICATIONS

- Cold and hot water in sanitary and heating installations.

ASSEMBLING INSTRUCTIONS

- Cut the pipe perpendicularly to its axis using an appropriate pipe-cutting tool.
- Remove possible residual burr.
- Insert nut and olive on the pipe.
- Insert the pipe into the body until the pipe stop.
- With an hexagonal spanner screw the nut. Pay attention to not exceeding in fitting clamping.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Devido ao constante desenvolvimento dos nossos produtos, o desenho e os dados fornecidos podem ser alterados sem aviso prévio.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.1-09.23

2/2