


BOBINE LATÃO - ACABAMENTO LATÃO

BRASS NIPPLE - BRASS FINISH



INFORMAÇÃO TÉCNICA - TECHNICAL INFORMATION

DN	COD.	DIMENSÕES - DIMENSIONS		Peso aprox. Weight aprox. (g)
		L (mm)	G (inches)	
1/2"x50	LSN00503	50	1/2"	58
1/2"x60	LSN00603	60	1/2"	79
1/2"x70	LSN00703	70	1/2"	86
1/2"x80	LSN00803	80	1/2"	101
1/2"x90	LSN00903	90	1/2"	113
1/2"x100	LSN01003	100	1/2"	127
1/2"x150	LSN01503	150	1/2"	200
1/2"x200	LSN02003	200	1/2"	268
1/2"x250	LSN02503	250	1/2"	342
3/4"x50	LSN00504	50	3/4"	73
3/4"x60	LSN00604	60	3/4"	91
3/4"x70	LSN00704	70	3/4"	127
3/4"x80	LSN00804	80	3/4"	126
3/4"x90	LSN00904	90	3/4"	165
3/4"x100	LSN01004	100	3/4"	166
3/4"x150	LSN01504	150	3/4"	255
3/4"x200	LSN02004	200	3/4"	359
3/4"x250	LSN02504	250	3/4"	457
1"x50	LSN00505	50	1"	100
1"x60	LSN00605	60	1"	142
1"x70	LSN00705	70	1"	158
1"x80	LSN00805	80	1"	203
1"x90	LSN00905	90	1"	243
1"x100	LSN01005	100	1"	258
1"x125	LSN01255	125	1"	315
1"x150	LSN01505	150	1"	383
1"x200	LSN02005	200	1"	542
1"x250	LSN02505	250	1"	685

Rev.0-08.25
1/2



Polígono Industrial ATUSA - Agurain S/N - 01200 Salvatierra (Alava) España
Tel.: (+34) 945 18 00 00 Fax : (+34) 945 30 01 53 e-mail: ventas@atusagroup.com
www.atusagroup.com

BOBINE LATÃO - ACABAMENTO LATÃO

BRASS NIPPLE - BRASS FINISH



INFORMAÇÃO TÉCNICA - TECHNICAL INFORMATION

DN	COD.	DIMENSÕES - DIMENSIONS		Peso aprox. Weight aprox. (g)
		L (mm)	G (inches)	
1 1/4"x50	LSN00506	50	1 1/4"	136
1 1/4"x60	LSN00606	60	1 1/4"	171
1 1/4"x70	LSN00706	70	1 1/4"	206
1 1/4"x80	LSN00806	80	1 1/4"	241
1 1/4"x90	LSN00906	90	1 1/4"	277
1 1/4"x100	LSN01006	100	1 1/4"	313
1 1/4"x125	LSN01256	125	1 1/4"	400
1 1/4"x150	LSN01506	150	1 1/4"	486
1 1/4"x200	LSN02006	200	1 1/4"	659
1 1/4"x250	LSN02506	250	1 1/4"	959
1 1/2"x100	LSN01007	100	1 1/2"	383
1 1/2"x150	LSN01507	150	1 1/2"	598
1 1/2"x200	LSN02007	200	1 1/2"	812

CARACTERÍSTICAS BÁSICAS

- Corpo em latão CW617N-DW conforme NP EN 12165.
- Método de fabrico: Barra em latão.
- Roscas de união conformes NP EN ISO 7-1.
- Acessórios de acordo com a norma NP EN 1254-4.
- Gama de temperaturas de serviço: -20 a 130 °C.
- Pressão máxima de serviço: PN 25.

APLICAÇÕES GERAIS

- Água sanitária fria e quente.

INSTRUÇÕES DE MONTAGEM

- Aplicar na rosca teflon ou vedante similar para obter uma maior estanquidade na união.
- Evitar o excesso de material de vedação aplicado para prevenir possíveis roturas causadas por aperto excessivo.
- Montar o acessório na instalação, tendo em atenção nunca apertar excessivamente mesmo.

Observações:

Dada a complexidade, variedade e grande quantidade de especificações particulares de cada instalação, em conjugação com a existência de diversos factores que podem afectar as condições de trabalho e natureza do produto, é da responsabilidade do utilizador final realizar os ensaios necessários para garantir o correcto funcionamento do produto em cada aplicação concreta. A instalação do produto deverá ser realizada e mantida seguindo os códigos de boa prática e/ou normas existentes.

BASIC FEATURES

- Body in brass CW617N-DW according to EN 12165.
- Production method: Brass bar.
- Threads according to EN ISO 7-1.
- Fittings comply with EN 1254-4 standard.
- Working temperature range: -20 to 130 °C.
- Maximal working pressure: PN 25.

GENERAL APPLICATIONS

- Cold and hot sanitary water.

ASSEMBLING INSTRUCTIONS

- Place over the fitting PTFE or similar sealant in order to obtain a better tightness on the coupling.
- Avoid any surplus of sealant in order to prevent possible breakings caused by excessive clamping.
- Connect the fitting with the installation. Pay attention to not exceeding in fitting clamping.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application. Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Devido ao constante desenvolvimento dos nossos produtos, o desenho e os dados fornecidos podem ser alterados sem aviso prévio.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.0-08.25
2/2



Polígono Industrial ATUSA - Agurain S/N - 01200 Salvatierra (Alava) España
Tel.: (+34) 945 18 00 00 Fax : (+34) 945 30 01 53 e-mail: ventas@atusagroup.com
www.atusagroup.com